

# Primer 20

## Porous surface primer

### Description

Primer 20 is a high performance single component chemically active, non-toxic liquid for brush application to prime porous surfaces.

### Advantages

- Easy to Apply
- Strong adhesion

### Application

Open tin lid. Mix thoroughly until a homogeneous dispersion is achieved.

Apply one thin coat using a clean dry brush. Avoid over application of primer causing puddles in the bottom of the joint. Sealants must be applied when the primer has become touch dry, that is after the evaporation of the solvent, but before the primer film has completely reacted. If the primer film has become completely tack free, the surfaces must be reprimed before applying the sealant.

### Cleaning

Clean equipment immediately after use with Nitoflor Sol.

### Estimating

### Supply

|           |                              |
|-----------|------------------------------|
| Primer 20 | : 250 ml, 500 ml & 1 ltr can |
|-----------|------------------------------|

### Coverage

|           |                     |
|-----------|---------------------|
| Primer 20 | : 8 - 10 sq.m/litre |
|-----------|---------------------|

### Storage

### Shelf life

12 months if stored in the original unopened packs in a cool dry place. Do not store in direct sunlight.

## Precautions

### Health and Safety

Primer 20 is flammable liquid. Shall be stored away from heat. and shall not be used near a naked flame. Skin contact shall be avoided. Eye protection and impervious rubber or PVC gloves shall be worn. Splashes must be washed off immediately. Prolonged breathing of vapour shall be avoided.

Hands shall be washed thoroughly before eating or smoking.

In the case of eye contact, medical attention shall be sought immediately.

### Disposal

Dispose according to local authority regulations. Do not dispose down drains or into local waterways.

For further information on any of the above, please consult your local Fosroc office - as below

### Additional information

|                              | Primer 20               |
|------------------------------|-------------------------|
| Flash point:                 | >50°C                   |
| Storage life :               | 12 months<br>@ 5 - 25°C |
| Drying time:                 | 20 to 60 mins.          |
| Flash point - Nitoflor Sol : | 33°C                    |

For further info please contact your local Fosroc office

# Primer 20

---



## Fosroc Chemicals (India) Pvt. Ltd.

### Head Office

Embassy Point, No. 150,  
2nd Floor, Infantry Road,  
Bangalore 560 001,  
Karnataka

### Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

### telephone

+91 80-42521900

### fax

+91 80-22281510

### e-mail

enquiry.india@fosroc.com

### Regional Offices

#### Chennai

Hills Centre, Old No 5,  
New No 9, 3rd Cross Street,  
Jeth Nagar, Raja Annamalaipuram,  
Chennai 600 028.  
Ph: +91 44 61304500

#### Mumbai

MBC Park, 12th floor, Office No.12B,  
'D' Block, Near G Corp/Hyper City  
Kasarwadawali, Ghodbunder Road,  
Thane (West) 400 615  
Ph: +91 22 6229 6800  
Fax: 022 62296809

#### Noida

Unit No. 601, Highway Tower-II  
A-13/2, 6th Floor, Sector- 62  
Gautam Buddha Nagar,  
Noida 201 309, Uttar Pradesh  
Ph: +91 120 6121900  
Fax: 0120-4270622

#### Kolkata

304, Jodhpur Park  
Kolkata 700 068  
Ph: +91 33-65343188  
Fax: 033-2499-0280