

CICO SEALANT PRIMER

SINGLE COMPONENT PRIMER FOR SEALANT

CICO SEALANT PRIMER is a single component solvent based primer to provide excellent bonding of sealant with substrate.

USES

This system is generally recommended as Primer coat on concrete substrate.

TECHNICAL DATA

Component	Single component
Curing	Touch Dry - 2-4 hrs.
	Hard Dry - 10 hrs.
	Recoat Time - 6 hrs. (Max.)
Specific Gravity	1.08 + 0.01
Coating Thickness	Approx. 75 microns in one coat.
Coverage	10 sq.mtr/ltr.

CICO Ultracem- 170 has a well-defined and steep particle size distribution with Blaine's specific surface area 6500-7000 cm²/g and maximum particle size of 18µm as compared to 60-80µm for ordinary Portland cement (OPC).

APPLICATION :- By brush

Surface Preparation

The area to be coated must be sound, clean and free from oil, grease or any other surface contaminants. Remove any loose materials or laitance by scraping, chipping, mechanical abrasion or any other suitable methods.

Visible cracks, depressed or any porous substrates are to be filled or leveled either with epoxy putty or acrylic based filler for concrete before application of sealant.

PACKING

Available in 1 ltr pack.

Important Note:

All CICO products are sold in the market after strict Quality Control in line of ISO 9001 and guaranteed against any manufacturing defect. Although the basic formulation of Company's products generally remains unchanged, production refinements arising from continuing research and evaluation program may occasionally result in marginal changes in properties. CICO aspires to ensure that any recommendation, advice, test data, specification, method statement and other information given in this product datasheet is accurate and best of company's knowledge. Since, the company (CICO TECHNOLOGIES LTD) has no control over the selection of its product, applicators, application methodology, how and where it is applied, therefore, the company cannot accept any liability directly or indirectly arising from the use of its product. It is important to any customer, user or specifier satisfies him / herself that the product is suitable for the intended purpose including health, safety and environmental aspect. Unless or otherwise agreed in writing, all products of the company are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. All customers, users, specifiers should ensure that they examine the suitability of the product with company's latest product data sheet.

CICO TECHNOLOGIES LIMITED

Corp. Office: C-120, 2nd Floor, Okhla Industrial Area,
Phase -I, New Delhi-110 020
Tel. No: 91-11-4050 9400, Fax: 91-11-4050 9413
E-Mail: cicotech@cicogroup.com
Web Site: www.cicogroup.com

